## LZR Fit as of 8/1/2018

Estimated amount of thining from forming heads										
head	2:1 Ellip									
thickness	10ga	7ga	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"
Head Ø										
18			0.0	)35						
24				0.035						
36							0.070 0.080			
48				0.0	045			0.080		
60				0.0	J4J				0.090	
72										
84				0.0	050				0.130	
96			0.060						0.105	
108			0.000						0.103	
120			0.040 0.063			62	0.068	0.070	0.110	0.140
144			0.040			0.008	0.070	0.110	0.140	

Estimated amount of thining from forming heads										
head	80:10 & ASME High Crown									
thickness	10ga	7ga	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"
Head Ø										
18										
24										
36										
48										
60										
72			0.0	)50	0.063					
84							0.080	0.090		
96										
108										
120										
144										

Estimated amount of thining from forming heads										
head	ASME & STD F&D									
thickness	10ga	7ga	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"
Head Ø										
18										
24			0.035							
36			0.033		0.040					
48					0.040					
60										
72							0.065			
84										
96							0.			
108			0	.045	0.050					
120								0.115		
144										
150								0.090		
156						0.090				

For other head types please contact: LZR FIT Customer Care | 715.453.5326 | info@lzrfit.com

Phone: 715-453-5326 Email: info@lzrfit.com Website: www.lzrfit.com